



不锈钢旋转吊环



- 旋转吊环材质为不锈钢。
- 不锈钢旋转吊环能满足用户更严苛的吊装环境。
- 不锈钢旋转吊环能满足用户更高的安全性能。
- 由内六角扳手拧紧，双衔接，结构紧凑，符合人体工程学。

| 产品编号 | 规格 | 工作载荷 5:1 WLL(T) | 工作载荷 4:1 WLL(T) | L1 (mm) | 扭矩 (NM) | S (mm) | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | 单重 (kg) |
|---------|---------|-----------------------|-----------------------|------------|------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|
| UQ06-01 | M24X3 | 2.7 | 2.7 | 36 | 160 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.2 |
| UQ06-02 | M30X3.5 | 3.5 | 3.5 | 45 | 250 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.2 |
| UQ06-03 | M33X3.5 | 3.5 | 3.5 | 50 | 250 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.2 |
| UQ06-04 | M36X4 | 5.0 | 5.0 | 54 | 320 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.2 |
| UQ06-05 | M36X3 | 5.0 | 5.0 | 54 | 320 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.2 |
| UQ06-06 | M39X4 | 5.0 | 5.0 | 54 | 320 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.4 |
| UQ06-07 | M42X4.5 | 6.0 | 6.0 | 63 | 400 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.4 |
| UQ06-08 | M42X3 | 6.0 | 6.0 | 63 | 400 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.4 |
| UQ06-09 | M45X4.5 | / | 6.0 | 63 | 400 | 19 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 5.7 |
| UQ06-10 | M48X5 | / | 6.4 | 68 | 600 | 19 | 79 | 38 | 90 | 123 | 91 | 182 | 41 | 11.0 |
| UQ06-11 | M48X3 | / | 6.4 | 68 | 600 | 19 | 79 | 38 | 90 | 123 | 91 | 182 | 41 | 11.0 |
| UQ06-12 | M48X4 | / | 6.4 | 68 | 600 | 19 | 79 | 38 | 90 | 123 | 91 | 182 | 41 | 11.0 |
| UQ06-13 | M52X5 | / | 6.4 | 68 | 600 | 19 | 79 | 38 | 90 | 123 | 91 | 182 | 41 | 11.2 |
| UQ06-14 | M56X5.5 | / | 8.0 | 78 | 600 | 19 | 79 | 38 | 90 | 123 | 91 | 182 | 41 | 11.3 |
| UQ06-15 | M56X4 | / | 8.0 | 78 | 600 | 19 | 79 | 38 | 90 | 123 | 91 | 182 | 41 | 11.4 |